
ASSEMBLY INSTRUCTIONS



Ancram XL Chandelier

Item # RL 5792

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

TOOLS REQUIRED (NOT INCLUDED):

Phillips Screwdriver Slotted Screwdriver Wire Cutters Wire Strippers

- 1. Carefully remove all parts from the box. Place on a clean, soft surface.
- 2. Remove collar loop (**D**) from canopy (**F**) by removing collar ring (**G**).
- 3. Install mounting plate **(B)** to the junction box and secure with mounting screws (C).
- 4. Secure collar loop **(D)** to mounting plate **(B)** using pliers to tighten locknut.
- 5. Install canopy (F) to collar loop (D) and secure with collar ring (G).
- 6. Feed electrical and ground wires through bottom rod (H3) and connect to fixture loop (I). Repeat for rods (H2 & H3), connecting together using loops (E).
- 7. Continue feeding wires though top rod (H1) and connect to rod (H2) and collar loop (D) using loops (E).
- 8. Cut excess wires, being sure to leave enough to reach the junction box. Separate wires, and strip insulation on each 5/8".
- 9. Loosen collar ring (G) and let canopy (F) slip down and rest on fixture loop (I).
- 10. Twist all fixture wires together. Slip through center hole of collar loop (D).

NOTE: Untwist wires and separate to prepare for connection.












ASSEMBLY INSTRUCTIONS



Ancram XL Chandelier

Item # RL 5792

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

11. Wrap fixture ground wire (bare copper) around the green grounding screw (see diagram 1). Tighten. Continue fixture ground wire and connect to supply ground wire (usually green or bare copper) using wire nut (A).

NOTE: It is imperative that the fixture is grounded.

- 12. Connect fixture neutral wire (ribbed) to the supply neutral wire (usually white) using wire nut (A).
- 13. Connect fixture hot wire (smooth with markings) to the supply hot wire (usually black) using wire nut (A).

CAUTION: Do not reverse the hot and neutral connections.

- 14. Make sure all wire connections are tight, then carefully tuck into the canopy.
- 15. Install canopy (F) to collar loop (D) and secure with collar ring (G).
- 16. Install light bulbs into the sockets.

Care Instructions: Clean only with a soft dry cloth or feather duster. Do Not use abrasive or chemical agents.



