


ASSEMBLY INSTRUCTIONS



Halo 5.5" Solitaire Flush Mount

Item # BBL4092

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

TOOLS REQUIRED (NOT INCLUDED):

Phillips Screwdriver Slotted Screwdriver

1. Carefully remove all parts from the box. Place on a clean, soft surface.
2. Remove shade (D) from fixture (A) by removing screws (C).
3. Connect fixture ground wire to supply ground wire (usually green or bare copper) using wire nut (E).
NOTE: It is imperative that the fixture is grounded.
4. Connect fixture neutral wire (white) to the supply neutral wire (usually white) using wire nut (E).
5. Connect fixture hot wire (black) to the supply hot wire (usually black) using wire nut (E).
CAUTION: Do not reverse the hot and neutral connections.
6. Install fixture (A) to junction box and secure with mounting screws (B).
7. Install shade (D) to fixture (A) and secure with screws (C).

CARE INSTRUCTIONS: Clean only with a soft dry cloth or feather duster. Do not use abrasive or chemical agents.